

PCBA assembly capability SMT & PCBA Capability

Material Type	Item	Min	Max
PCB	Dimension	50*50*0.6	400*339*3
	Weight		1.8KG
	Special		590*280*3
	Material	FR-4, CEM-1, CEM-3, Aluminium-	
	Surface finish	HAL,OSP,Immersion gold,Flash	
Components	Chip & IC	01005 (0.6* 0.3)	22*22
	Special size	1.6*0.8	72mm
	BGA Pitch	0.35mm	1.0mm
	QFP Pitch	0.35mm	1.0mm
Components Type	Speed(CPH)	Accuracy(mm)	Camera
1608Chip	52K/H	0.04	Fly Camera
1005Chip	52K/H	0.04	Fly Camera
0603Chip	52K/H	0.04	Fly Camera
SOP16	30K/H	0.10	Fly Camera
QFP100	20K/H	0.03	Fixture Camera
QFP256	10K/H	0.03	Fixture Camera
BGA	10K/H	0.03	Fixture Camera
Product Type	Qty	Normal lead time	Quick-turn lead time
SMD+connector	5~200	6WD	3WD
SMD+connector	201~2000	7WD	7WD
SMD+connector	≥ 2000	7 ~ 9WD	8 WD
SMD+DIP	5~200	5WD	4WD
SMD+DIP	201~2000	7WD	5 WD
SMD+DIP	≥ 2000	8WD	6 WD
Remark: The above lead time			

YAMAHA YSM20R SMT ASSEMBLY MACHINE CAPABILITY

SAMSUNG SM421			
Material Type	Item	Min	Max
PCB	Dimension	50*50*0.6	400*339*3
	Weight		1.8KG
	Special		590*280*3
	Material	FR-4, CEM-1, CEM-3, Aluminium-	
	Surface finish	HAL,OSP,Immersion gold,Flash	
Components	Chip & IC	01005 (0.6* 0.3)	22*22
	Special size	1.6*0.8	72mm
	BGA Pitch	0.3mm	1.0mm
	QFP Pitch	0.3mm	1.0mm
Components Type	Speed(CPH)	Accuracy(mm)	Camera
1608Chip	52K/H	0.04	Fly Camera
1005Chip	52K/H	0.04	Fly Camera
0603Chip	52K/H	0.04	Fly Camera
SOP16	30K/H	0.10	Fly Camera
QFP100	20K/H	0.03	Fixture Camera
QFP256	10K/H	0.03	Fixture Camera
BGA	10K/H	0.03	Fixture Camera
YAMAHA YSM20R			
High Efficiency,High Reliability and High			
1.Micro Chip			
2.High Efficiency for the PCB			
3.autofeeder;			
4.Mega Pixel Camera (Fly			
5.Antistatic nozzle;			
6.The minimum size 01005.			